


ASME B18.6.3- 2013

Nominal Size	A		H		J		T		M	Recess Penetration Gaging Depth		Phillips Driver Size
	Head Diameter		Head Height		Slot Width		Slot Depth			Ref	Max	
	Max	Min	Max	Min	Max	Min	Max	Min				
6	.260	.240	.103	.091	.048	.039	.068	.051	.155	.073	.045	2
8	.309	.287	.120	.107	.054	.045	.077	.058	.171	.090	.064	2
10	.359	.334	.137	.123	.060	.050	.087	.065	.188	.108	.082	2
1/4	.472	.443	.175	.160	.075	.064	.109	.082	.261	.130	.104	3
5/16	.590	.557	.216	.198	.084	.072	.132	.099	.301	.170	.144	3
3/8	.708	.670	.256	.237	.094	.081	.155	.117	.380	.208	.182	4



ASME B18.6.3- 2013

Nom Size	A		H		F		U		J		D		P	M	Recess Penetrating Gaging Depth		Phillips Driver Size
	Width Across Flats		Head Height		Washer Diameter		Washer Thickness		Slot Width		Slot Depth				Protrusion Beyond Gaging Ring	Recess Diameter	
	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Min	Ref			
6	.250	.244	.093	.080	.328	.302	.025	.015	.048	.039	.053	.033	.048	.148	.089	.064	2
8	.250	.244	.110	.096	.348	.322	.031	.019	.054	.045	.074	.052	.058	.168	.115	.090	2
10	.312	.305	.120	.105	.414	.384	.031	.019	.060	.050	.080	.057	.063	.178	.127	.102	2
12	.312	.305	.155	.139	.432	.398	.039	.022	.067	.056	.103	.077	.083	.247	.152	.127	3
1/4	.375	.367	.190	.172	.520	.480	.050	.030	.075	.064	.111	.083	.103	.277	.186	.161	3