



3-PRONG

3-PRONG T-NUTS, STRAIGHT BARREL

Part Number**	Thread Size	H	G	F	A	T	Drill Size	Part Number**	Thread Size	H	G	F	A	T	Drill Size
		Barrel Height (±1/32)	Flange Diam. (±1/32)	Barrel Diam. (±.015)	Prong Height (±1/32)	Material Thickness (±.015)				Barrel Height (±1/32)	Flange Diam. (±1/32)	Barrel Diam. (±.015)	Prong Height (±1/32)	Material Thickness (±.015)	
0402NT3	4-40	1/8	23/64	.130	3/32	.024	9/64	1406NT3	1/4-20	3/8	3/4	.305	1/4	.047	5/16
0404NT3	4-40	1/4	23/64	.141	3/32	.031	9/64	1407NT3	1/4-20	7/16	3/4	.305	5/16	.047	5/16
0604NT3	6-32	1/4	1/2	.188	1/8	.035	13/64	1408NT3	1/4-20	1/2	3/4	.305	7/32-1/4	.047	5/16
0804NT3	8-32	1/4	23/32	.208	7/32	.030	7/32	1409NT3	1/4-20	9/16	3/4	.305	7/32	.047	5/16
0805NT3	8-32	5/16	3/4	.208	1/4	.035	7/32	3105NT3	5/16-18	5/16	7/8	.360	9/32	.047	3/8
1004NT3	10-24	1/4	3/4	.243	5/32	.039	1/4	3106NT3	5/16-18	3/8	7/8	.390	1/4	.063	25/64
1005NT3	10-24	5/16	3/4	.243	7/32	.040	1/4	3107NT3	5/16-18	7/16	7/8	.390	1/4	.063	13/32
1007NT3	10-24	7/16	3/4	.243	5/16	.040	1/4	3108NT3	5/16-18	1/2	7/8	.360	1/4	.063	3/8
1105NT3	10-32	5/16	3/4	.243	7/32	.040	1/4	3110NT3	5/16-18	5/8	7/8	.390	5/16	.063	25/64
1106NT3	10-32	3/8	3/4	.243	1/4	.040	1/4	3705NT3	3/8-16	5/16	1	.420	9/32	.063	27/64
1107NT3	10-32	7/16	3/4	.243	5/16	.040	1/4	3707NT3	3/8-16	7/16	1	.440	11/32	.063	29/64
1404NT3	1/4-20	1/4	3/4	.305	3/16	.047	5/16	3710NT3	3/8-16	5/8	1	.440	9/32	.063	29/64
1405NT3	1/4-20	5/16	3/4	.305	7/32	.047	5/16								

**Last digit of part number denotes number of prongs.

Description	Internally threaded barrel-shaped fasteners integrally formed with a flat base, which has prong-type projections extending perpendicular from the base aside the barrel.
Applications/Advantages	Used for fastening metal to products made of wood, particle board or plastic. The 3-prong style is used in harder materials to minimize splitting of the mating surface.
Material	C1004-10 low-carbon steel.

NOTE: There is no single standard for T-nut dimensions. These values are offered as a guide; deviations from these specifications may occur.