



### 4-PRONG

#### T-NUTS, STRAIGHT BARREL

Part Number**	Thread Size	H	G	F	A	T	Drill Size	Part Number**	Thread Size	H	G	F	A	T	Drill Size
		Barrel Height (±1/32)	Flange Diam. (±1/32)	Barrel Diam. (±.015)	Prong Height (±1/32)	Material Thickness (±.015)				Barrel Height (±1/32)	Flange Diam. (±1/32)	Barrel Diam. (±.015)	Prong Height (±1/32)	Material Thickness (±.015)	
0604NT4	6-32	1/4	1/2	.188	1/8	.035	13/64	1408NT4	1/4-20	1/2	3/4	.305	7/32	.047	5/16
0804NT4	8-32	1/4	23/32	.208	3/16	.031	7/32	1409NT4	1/4-20	9/16	3/4	.305	1/4	.047	5/16
0805NT4	8-32	5/16	3/4	.208	1/4	.035	7/32	1410NT4	1/4-20	5/8	3/4	.306	1/4	.047	5/16
0806NT4	8-32	3/8	3/4	.208	1/4	.035	7/32	3105NT4	5/16-18	5/16	7/8	.360	9/32	.047	3/8
0807NT4	8-32	7/16	3/4	.208	1/4	.035	7/32	3106NT4	5/16-18	3/8	7/8	.390	1/4	.063	25/64
1005NT4	10-24	5/16	3/4	.243	7/32	.040	1/4	3107NT4	5/16-18	7/16	7/8	.360	1/4	.047	3/8
1007NT4	10-24	7/16	23/32	.243	7/32	.040	1/4	3108NT4	5/16-18	1/2	7/8	.390	1/4	.063	13/32
1105NT4	10-32	5/16	3/4	.243	7/32	.040	1/4	3110NT4	5/16-18	5/8	7/8	.375-.390	1/4-5/16	.060-.063	3/8, 25/64
1106NT4	10-32	3/8	3/4	.243	1/4	.043	1/4	3112NT4	5/16-18						
1107NT4	10-32	7/16	3/4	.243	7/32	.043	1/4	3705NT4	3/8-16	5/16	1	.440	9/32	.063	27/64
1404NT4	1/4-20	1/4	3/4	.305	7/32	.047	5/16	3707NT4	3/8-16	7/16	1	.440	11/32	.063	29/64
1405NT4	1/4-20	5/16	3/4	.305	7/32	.047	5/16	3710NT4	3/8-16	5/8	1	.440	5/16	.063	29/64
1406NT4	1/4-20	3/8	3/4	.305	7/32	.047	5/16	3716NT4	3/8-16						
1407NT4	1/4-20	7/16	3/4	.305	1/4	.047	5/16								

\*\*Last digit of part number denotes number of prongs.

<b>Description</b>	Internally threaded barrel-shaped fasteners integrally formed with a flat base, which has prong-type projections extending perpendicular from the base aside the barrel.
<b>Applications/ Advantages</b>	Used for fastening metal to products made of wood, particle board or plastic. Four prong tee-nuts can be used in hard or soft woods.
<b>Material</b>	C1004-10 low-carbon steel.
<b>Plating</b>	See Appendix-A for plating information.

NOTE: There is no single standard for T-nut dimensions. These values are offered as a guide; deviations from these specifications may occur.